



Implementation of Foamed Bitumen in Queensland – a 25-year journey

Damian Volker, Principal Engineer



Department of Transport and Main Roads (TMR)



Australian Pavement Recycling and Stabilisation Conference

Pavement Recycling for Sustainable Roads

Novotel Brighton Beach, Sydney • 10th August 2022



Traditional Owners Acknowledgement

TMR Artwork storyline Travelling by Gilimbaa.



About us



Implementation of Foamed Bitumen in Queensland



Strong and flexible pavement

Moisture resistant pavement



Reduces shrinkage cracking

Using lime as a secondary additive



Australian Pavement Recycling and Stabilisation Conference
Pavement Recycling for Sustainable Roads
Novotel Brighton Beach, Sydney • 10th August 2022



TMR early Foamed Bitumen projects

Border (Warwick) District

-1997 – 1999: 3 projects

North Coast Hinterland District

-1998: 1 project

South Coast Hinterland District

-2000/01: 2 projects

Redland Shire

-2000: 2 projects



**Australian Pavement Recycling
and Stabilisation Conference**

Pavement Recycling for Sustainable Roads

Novotel Brighton Beach, Sydney • 10th August 2022



Pavement Recycling and Stabilisation Association

The first trial - Gladfield – Constructed 1997

- 250mm OWP + 200mm IWP stabilised with 4% bitumen and 1.5% cement
- CBR 3 (expansive) subgrade
- Pavement life (prior to fatigue) ~ 2.5 years
- Approx. traffic to failure ~ 2.5×10^6 ESA
- Site has been overlaid with 160mm granular material.



**Australian Pavement Recycling
and Stabilisation Conference**

Pavement Recycling for Sustainable Roads


Novotel Brighton Beach, Sydney • 10th August 2022



Pavement Recycling and Stabilisation Association

TMR foamed bitumen laboratory equipment

Herston
(Then)



Bulwer Island
(Now)



Inglewood – Constructed 1998

- 200mm stabilised layer with 4% bitumen and 1.5% quicklime.
- Insitu subgrade strength CBR 5 – 20
- 3 year prior to the onset of fatigue cracking (only in areas with insitu CBR 5 - 8)
- Calculated fatigue life similar to that achieved in the field



**Australian Pavement Recycling
and Stabilisation Conference**

Pavement Recycling for Sustainable Roads

Novotel Brighton Beach, Sydney • 10th August 2022



Pavement Recycling and Stabilisation Association

Rainbow Beach – Constructed 1998

- Trial to assess foamed bitumen against bitumen emulsion stabilisation
- 3 x 200m sections of foamed bitumen stabilisation constructed using 3, 4 and 5% bitumen + 1.5% quicklime
- Still performing adequately and showing few signs of distress



**Australian Pavement Recycling
and Stabilisation Conference**

Pavement Recycling for Sustainable Roads

Novotel Brighton Beach, Sydney • 10th August 2022



Pavement Recycling and Stabilisation Association

Allora – Constructed 1999

- 17km section stabilised 250mm OWP + 200mm IWP with 3.5% bitumen + 1.5% quicklime
- Originally design with a 50 – 120mm asphalt overlay (not constructed)
- Subgrade – expansive black soil
- 1.5km section tested for deflection at regular intervals





**Australian Pavement Recycling
and Stabilisation Conference**

Pavement Recycling for Sustainable Roads

Novotel Brighton Beach, Sydney • 10th August 2022

Allora - 2002

- Isolated signs of distress
 - Two minor rut / shove failures
 - Possibly material related
- Longitudinal cracking
 - Subgrade movement
 - IWP fatigue cracking (insufficient depth?)
- Seal Flushing



**Australian Pavement Recycling
and Stabilisation Conference**

Pavement Recycling for Sustainable Roads

Novotel Brighton Beach, Sydney • 10th August 2022



Pavement Recycling and Stabilisation Association

The foamed bitumen discovery – flood resilience



Staplyton-Jacobs Well Road – after prolonged 1m deep flood waters.



**Australian Pavement Recycling
and Stabilisation Conference**

Pavement Recycling for Sustainable Roads

Novotel Brighton Beach, Sydney • 10th August 2022



Pavement Recycling and Stabilisation Association

The foamed bitumen discovery – flood resilience



Bruce Highway Yeppen Floodway



Mt. Lindesay Hwy (Camp-Cable Rd)



Cunningham Highway Warrill View



Oakey-Pittsworth Road Mt. Tyson

These foamed bitumen pavements survived unscathed after flooding from natural disasters in Qld.

Flood resilience

RoadTek project: Yandina – Bli Bli Road (May 2022)



After flooding - untreated section




After flooding foamed bitumen treated section

Queensland Government's objectives for the community



TMR meets these objectives by delivering resilient and cost effective foamed bitumen pavement solutions in collaboration with the stabilisation industry.

Foamed bitumen regional distribution in TMR



(ARRB, 2015)



Plant-mixed foamed bitumen - 2012



Plant-mixed foamed bitumen - 2022

KMA 220 Plant



Image sourced from Hiway Stabilizers, 2018

Batch Plant



Image provided by Fulton Hogan, 2021



Ammann Plant




Marini Plant



Image provided by Quarry Solutions, 2021

Pugmill/plant-mixed foamed bitumen (typically located at a quarry).

The challenges along the way



TMR's first Foamed Bitumen trial was in 1997, performed by Stabilised Pavements Australia.

Pavement recycling for sustainable roads



In situ stabilisation

Up to **6 000** tonnes of raw material *could be saved per km of road.*

In situ stabilisation of existing roads is undertaken by pulverising the road and mixing various stabilising agents (including cement, bitumen, fly ash and slag) which provides a strengthened rejuvenated pavement.

This results in very little waste sent to landfill without needing to consume new materials.



<https://www.tmr.qld.gov.au/Community-and-environment/Planningfor-the-future/Building-sustainable-roads>

Recycled materials - gravel specification for foamed bitumen

Construction and demolition waste (C&D)

Up to 8 000 tonnes of waste diverted from landfill per kilometre of road.

C&D waste is material recovered from construction and demolition sites such as concrete, brick and glass, and can be used as an alternative to natural aggregates and sand in road bases.

TMR is also investigating the use of C&D waste in concrete.

Table 7.2.1(a) – Constituents in Type 2 materials

Subtype	Maximum Limit of each Constituent (percent by mass)				
	Natural gravel or quarried material	Recycled materials			
		Recycled concrete	RAP	Recycled brick	Recycled glass ^
2.1	100	100	0	0	0
2.2	100		15	15	0
2.3	100		20	20	
2.4	100		45	45	20
2.5	100		45		

^ Recycled glass shall comply with the requirements of MRTS36 *Recycled Glass Aggregate*.

Glass

10 to 20% recycled glass can be used in roads.

TMR is finding ways to use recycled crushed glass as a substitute for sand and aggregate in road materials. Up to 10 per cent can be used in asphalt bases and up to 20 per cent in gravel bases.


TMR is investigating the use of recycled glass in concrete, as bedding and backfill sand around pipes..

Subtypes	2.1 and 2.2
Test Sieve Size (mm)	
75.0	100
37.5	100
19.0	87 – 100
9.5	67 – 87
4.75	50 – 70
2.36	36 – 52
0.425	14 – 24
0.075	7 – 16

<https://www.tmr.qld.gov.au/Community-and-environment/Planningfor-the-future/Building-sustainable-roads>

Petrographic analysis on materials for foamed bitumen

Geochem




PETROGRAPHIC REPORT
ON TWO FOAMED BITUMEN PAVEMENT PAT SAMPLES



DEPARTMENT OF TRANSPORT AND MAIN ROADS
PAVEMENT REHABILITATION, ENGINEERING & TECHNOLOGY



Client Ref: Damian Volker




Fly ash and blast furnace slag

Up to **70%** reduction in greenhouse gas emissions *from the use of fly ash.*

Fly ash and blast furnace slag are industrial wastes from coal fired power plants and steel production. These waste products can be used to replace up to 70 per cent of the cement used in pavements.

Up to 35 per cent of the cement used in structural concrete can be replaced with fly ash, up to 50 per cent with a combination of fly ash and slag, and 60 to 70 per cent with slag alone.



National Asset Centre of Excellence (NACOE)



**Australian Pavement Recycling
and Stabilisation Conference**

Pavement Recycling for Sustainable Roads

Novotel Brighton Beach, Sydney • 10th August 2022



Pavement Recycling and Stabilisation Association

Austrroads

New project: APT6245 Develop design procedures for foamed bitumen stabilised pavements.



Reference: Austrroads 2021

Follows on from:

- **APT6157 Laboratory fatigue characterisation of foamed bitumen stabilised materials and**
- **TT2046 Improving the cost effectiveness of foamed bitumen stabilised pavements**



**Australian Pavement Recycling
and Stabilisation Conference**

Pavement Recycling for Sustainable Roads

Novotel Brighton Beach, Sydney • 10th August 2022



Pavement Recycling and Stabilisation Association

How foamed bitumen is applied in Queensland



Floodways and areas of high rainfall



**Australian Pavement Recycling
and Stabilisation Conference**

Pavement Recycling for Sustainable Roads

Novotel Brighton Beach, Sydney • 10th August 2022

Yeppen Floodway Rockhampton South



Pavement Recycling and Stabilisation Association

Mt. Lindesay Highway – Camp Cable Road



April 2017



**Australian Pavement Recycling
and Stabilisation Conference**

Pavement Recycling for Sustainable Roads

Novotel Brighton Beach, Sydney • 10th August 2022




Pavement Recycling and Stabilisation Association

Mt. Lindesay Highway – Camp Cable Road



After April 2017



After February 2022



**Australian Pavement Recycling
and Stabilisation Conference**

Pavement Recycling for Sustainable Roads

Novotel Brighton Beach, Sydney • 10th August 2022



Pavement Recycling and Stabilisation Association

Motorways as a structural subbase in lieu of deep-lift asphalt



Logan Motorway 2007 – Westbound



Smith Street Motorway 2015 – Eastbound



New works (Greenfield) as well as rehabilitation



Airports and councils



Brisbane Airport



Scenic Rim Council



**Australian Pavement Recycling
and Stabilisation Conference**

Pavement Recycling for Sustainable Roads

Novotel Brighton Beach, Sydney • 10th August 2022



Pavement Recycling and Stabilisation Association

Rehabilitating old cement-treated pavements



Before



After

Bruce Highway 10E



In combination with lime or triple blend subbase




Learnings: Geosynthetics are a must on reactive subgrades.



Risks of environmental cracking over expansive subgrades



Risks and use of geosynthetics – design considerations



Learnings: Geosynthetics are a must on reactive subgrades.

Plant-mixed offers the opportunity to place geosynthetics under the imported foamed bitumen base.

Geogrid reinforced sprayed seals



**Australian Pavement Recycling
and Stabilisation Conference**


Pavement Recycling for Sustainable Roads

Novotel Brighton Beach, Sydney • 10th August 2022



Pavement Recycling and Stabilisation Association

Development of Foamed Bitumen design, testing and construction documents



Promotion of Foamed Bitumen technology at local, state, national and international levels




Consultation, training courses and project-linked onsite training



Emerging technologies and continual improvements to design and construction practices





W 380 CR (Paver Laid Insitu Foamed Bitumen)



50% Hydrated Lime : 50% Fly Ash blend = \$400/tonne


Research and Analysis - rigorous lab testing and field research




Foamed bitumen - workability

Foamed bitumen with: hydrated lime verses cement with regards to working time.

Dry density vs time – 2% lime



Dry density vs time - 2% GB 60/40



TMR research - with university students



Current and future challenges foamed bitumen faces in Qld

- Costs and availability of stabilising agents – what are TMR doing to assist.



Increasing the bitumen content to 3.5 per cent to increase fatigue resistance and reduce layer thickness.

Secondary additive: Hydrated lime typically 1.25 – 2 per cent, or 50:50 hydrated lime : fly ash blend* – typically 1.25 – 2 per cent.




Increased the use of Quicklime on subgrade and triple blend subbase projects.

**Optional, but often essential to meet modulus requirements.*

Bitumen economy - 0.5% increase saving costs

Result of increased bitumen from presumptive 3% bitumen by mass to 3.5% bitumen by mass – Re-modelled design depths



Scenario:

A project already designed based on 1800 MPa and 3% bitumen by mass (7% by volume). The 300mm depth as per the original 3% bitumen design is remodelled. The relationship between increased bitumen content and fatigue life results in a reduction in Foamed Bitumen depth.

1800MPa - 300mm - 3% bitumen by mass (7.0% by volume) = 20-year life

1800MPa - 286mm - 3.25% bitumen by mass (7.5% by volume) = 20-year life

1800MPa - 272mm - 3.5% bitumen by mass (8.0% by volume) = 20-year life

Stabilisation training modules on TMR specifications



Similar concept to the TfNSW (Transport for New South Wales) Grey Card system for:

- B80 Grey Card Training - Concrete Work for Bridges.
- Finish Concrete - Concrete Road Paver Crew training.



**Australian Pavement Recycling
and Stabilisation Conference**

Pavement Recycling for Sustainable Roads


Novotel Brighton Beach, Sydney • 10th August 2022



Pavement Recycling and Stabilisation Association

Summary

- These innovations and savings arise from rigorous laboratory and field research, and justify ongoing research.
- Pavement Rehabilitation Unit extensively use and appreciate the great value that our TMR laboratories provide for the department.
- This ensures that the implementation of responsible innovation is based on sound laboratory research.



**Australian Pavement Recycling
and Stabilisation Conference**

Pavement Recycling for Sustainable Roads

Novotel Brighton Beach, Sydney • 10th August 2022



Pavement Recycling and Stabilisation Association



Thank you and stay connected



TMRQld



@TMRQld



Department of Transport and Main Roads



TMRQld

13 QGOV (13 74 68)

www.tmr.qld.gov.au | www.qld.gov.au