


From Ground Up: Stabilisation's Impact on the Renewable Energy Transition

Joshua Mason Senior Associate / Lead Civil Engineer

Amy Pitt, Associate / Civil Designer / Vic Operations

icubed consulting




Australian Pavement Recycling and Stabilisation Conference

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024





Joshua Mason

Senior Associate | Lead Civil Engineer
B.Eng (Hons), CPEng, NER, RPEQ



Amy Pitt

Associate | Civil Designer | Vic Operations
B.Bus, Dip Bldg Design & Tech



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024






43%

Carbon Emissions reduction below
2005 levels by 2030

Australia has committed to achieving net
zero emissions by **2050**

Meeting this target entails the retirement of aging fossil fuel generators and their replacement with decentralised renewable energy infrastructure, such as solar and wind farms, supported by battery energy storage systems and other long-duration storage solutions, such as pumped hydro.



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



icubed consulting



Pavement Recycling and Stabilisation Association



Lincoln Gap Windfarm, 2018



Introduction to icubed



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Renewables Capability




Source: icubed, Dulacca Windfarm, 2018

icubed consulting have played a significant role in the Australian wind and solar industry for over **20 years**.

Since beginning as wind turbine foundation designers, our services now extend to providing specialised and expert advice, from conception to completion, on utility-scale wind and solar projects.

Our work encompasses planning, approvals management, civil and structural design for complete internal and external civil balance of plant (BOP) documentation, as well as onsite engineering and project management construction support.

We have delivered 7GW through 2000 tower bases of detailed design works and over 10GW in additional preliminary design works.



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



i3 Renewable Insights

01


We have been designing wind farms and other renewable energy projects for 20 years in ANZ

02

We have modelled nearly 4,000 turbines footing at various stages of project design life and 5,000km of access tracks

03

In 2020, icubed carried out the detailed design of 70% of the commissioned wind farms in Australia



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



icubed consulting



Pavement Recycling and Stabilisation Association




Wind farms generate electricity using wind turbines that convert kinetic energy from the wind into electrical energy.

Siting for wind turbines is crucial for optimising their efficiency in generating energy. Ideal sites are typically at higher elevations where wind speeds are generally stronger and more consistent.

Elevated locations capitalise on the natural increase in wind speed with altitude, owing to reduced surface friction. Moreover, these sites often have fewer obstructions that can disrupt wind flow, such as trees.

While our case studies focus on wind farms, we note that stabilisation has been utilised in Substations and Battery Energy Storage System (BESS) benches and Solar Farms.



**Australian Pavement Recycling
and Stabilisation Conference**


Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024





Source, Stringfellows, Turitea Wind Farm, 2020



**Australian Pavement Recycling
and Stabilisation Conference**



Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Lower Order Road vs Wind Farm Access Track

Equivalent Standard Axle Generation



Australian Pavement Recycling and Stabilisation Conference

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Pavement Recycling and Stabilisation Association

Over-Sized Over-Mass Vehicles



Crawler Crane

Source - icubed, Taralga Wind Farm, 2014



Transformer Delivery Vehicle

Source - Zenviron, Rye Park Wind Farm, 2022



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024





Case Study 1

Berrybank Wind Farm Stage 2

Source: GPG Naturgy Group, 2024



**Australian Pavement Recycling
and Stabilisation Conference**
Designing for Reuse and Resilience
Pullman King George Square, Brisbane • 7th August 2024



Site Geology



Source: icubed, Berrybank Wind Farm, 2021



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience


Pullman King George Square, Brisbane • 7th August 2024



The initial pavement solution proposed was a typical unbound pavement that would have variable thickness based on the subgrade strength encountered across the site.

PAVEMENT THICKNESS ASSESSMENT – Tracks and Hardstands		
Cu (kPa)	Pavement Thickness Required (mm) (Considering Imported Crushed Rock and Stabilised Subgrade)	
	Access Tracks	WTG Hardstands - Load 250kPa
<60	Consult Geotechnical Engineer for Advice	Consult Geotechnical Engineer for Advice
60	500	Consult Geotechnical Engineer for Advice
80	300	600
100	200*	300
120	200*	200*
120 - 200	200*	200*


To achieve suitable subgrade strengths, the adopted pavement solution utilised a lime-stabilised subgrade, with typically 3% lime. As a result, the access tracks were overlaid with a consistent 200mm of pavement material.



Australian Pavement Recycling and Stabilisation Conference

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Pavement Recycling and Stabilisation Association

Lime Stabilisation Application




Lime Application – Spreading over access track

Source - icubed, 2020



Lime Application - Mixing

Source - icubed, 2022



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Pavement Recycling and Stabilisation Association




45,000m³

Reducing the final imported pavement material by an estimated half




2,360

Truck and Dog round trips eliminated



1.8E04

ESA loads from the local public roads



Australian Pavement Recycling and Stabilisation Conference

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



icubed consulting



AustStab

Pavement Recycling and Stabilisation Association

WTG Foundation Treatment



Source: Agnew Mine Wind Farm, 2021



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



icubed consulting



Pavement Recycling and Stabilisation Association



Lal Lal Windfarm, 2019



Case Study 2

Lal Lal Wind Farm



Australian Pavement Recycling and Stabilisation Conference
Designing for Reuse and Resilience
Pullman King George Square, Brisbane • 7th August 2024



Ground Improvement for WTG's



Source: icubed, Footing Excavation Lal Lal Wind Farm, 2019



Source: icubed, Footing Excavation Lal Lal Wind Farm, 2019



Source: icubed WTG, 2021




Source: icubed, Blinding Concrete Pour, Lal Lal Wind Farm, 2019



Source: icubed, Concrete Pour, Lal Lal Wind Farm, 2019



Source: icubed, Partially Backfilled Footing, Kennedy Energy Park, 2018



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Excavation Problems

Over blasted &
Over excavated rock



Excavation inundated
with water



Source: icubed, Lal Lal Wind Farm, 2019



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



CTB Backfill

Cement-treated base (CTB) material provides an effective compromise between conventional pavement material and blinding concrete for backfilling applications.

It effectively addresses compaction and saturation challenges by harnessing the strength-enhancing properties of cement.

This solution not only mitigates construction complexities but also minimises resource scarcity concerns, as CTB generally requires less cement than blinding concrete and pavement materials respond well to CTB.



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience


Pullman King George Square, Brisbane • 7th August 2024



Stabilisation Future Opportunities



Source, Stringfellows, Turitea Wind Farm, 2020



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Potential for Stabilisation in Steep Access Track Grades



One of the most promising applications for stabilisation on wind farm sites lies in addressing steep to very steep access track grades. The decision to apply treatments such as unsealed pavements with sealing or binding to enhance traction for OSOM vehicles and ensure site user safety varies from project to project. Generally, treatment is recommended for pavements with longitudinal slopes ranging from 12% to 18%.

Source: icubed, Lincolns Gap Wind Farm, 2021



Australian Pavement Recycling and Stabilisation Conference

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



icubed consulting



Pavement Recycling and Stabilisation Association

Challenges and Maintenance



Pavement Rutting On a Gentle Graded Access Track

Source - icubed, Turitea Wind Farm, 2022



CTB Treated Access Track – Grades >15%

Source - icubed, Turitea Wind Farm, 2022



Australian Pavement Recycling and Stabilisation Conference

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



icubed consulting




Pavement Recycling and Stabilisation Association

Remote Sites & Long Haulage



Source, Stringfellows, Turitea Wind Farm, 2020



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience


Pullman King George Square, Brisbane • 7th August 2024





Stabilisation techniques have proven pivotal in optimising project outcomes across diverse terrains, enhancing subgrade materials performance and reducing reliance on imported pavement materials

Looking ahead, these growing challenges presents the stabilisation industry with a unique opportunity to innovate, market solutions, and deploy treatments that can withstand the heavy loadings of construction phase, while remaining resilient against environmental factors and maintaining the stabilised properties through subsequent maintenance activities.



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024





icubed consulting

innovation ingenuity inspiration

W: www.icubed.com.au

E: mail@icubed.com.au



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024

