


Improved Design & Construction Methodology for Urban Local Roads in Flood Prone Areas

Scott Young, National Technical Manager

BE(Hons), MPavtTech, RPEng(Civil), RPEQ, RPEV

Stabilised Pavements of Australia



Australian Pavement Recycling and Stabilisation Conference

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Co - Authors


Zach Fryer

- *BE (Civil)*
- Construction Coordinator
- Byron Shire Council



Andrew Middleton

- *ADip (Civil)*
- Regional Manager, Northern NSW
- Stabilised Pavements of Australia



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Scope

- Introducing River Terrace
 - Site Condition and Constraints
- Design
 - Rehabilitation Pavement Design
 - Construction Process
 - Mix Design
- Construction Phase and Post Construction Testing
- Project Economics
- Conclusion



**Australian Pavement Recycling
and Stabilisation Conference**


Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Pavement Recycling and Stabilisation Association

River Terrace



**Australian Pavement Recycling
and Stabilisation Conference**


Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Pavement Recycling and Stabilisation Association

Site Condition & Constraints



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience


Pullman King George Square, Brisbane • 7th August 2024



Rehabilitation Pavement Design

Layer	Details
Spray Seal	Double/Double (14mm/7mm aggregate)*
Priming Treatment	Cutback primer, AMC0 or AMC00
Base Course – DGB20	150 mm - CBR 35%
Subbase Course – DGS20 or DGS40	300 mm - CBR 25%
Natural Subgrade - Silty CLAY (CH)	CBR 4%
* A 40 mm thick asphalt seal (AC10) may also be acceptable as a seal if preferred by Council.	

Layer	Details
Spray Seal	Double/Double (14mm/7mm aggregate)*
Priming Treatment	Cutback primer, AMC0 or AMC00
Base Course – DGB20	150 mm - CBR 35%
Subbase Course – DGS20 or DGS40	150 mm - CBR 25%
Lime Stabilised Subgrade Insitu – 5% Lime Content	200 mm - CBR 10%
Natural Subgrade – Silty CLAY (CH)	CBR 4%
* A 40 mm thick asphalt seal (AC10) may also be acceptable as a seal if preferred by Council.	



**Australian Pavement Recycling
and Stabilisation Conference**


Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Pavement Recycling and Stabilisation Association

Recommended Construction Process



Australian Pavement Recycling and Stabilisation Conference


Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Pavement Recycling and Stabilisation Association


Mix Design



- a) Conduct Lime Demand (LD) test on subgrade clay.
- b) Adopt lime content of LD+1%.
- c) Breakdown all samples together to ensure accurate proportions of the bituminous wearing course, base gravel and subgrade are contained in the mixture. This was to reflect the initial prepulverising and crossblending phase.
- d) Determine OMC/MDD with LD+1% hydrated lime.
- e) Mix hydrated lime at LD+1% at OMC.
- f) Prepare UCS cylinders.
- g) Cure the samples whilst in the cylinders at 25 degrees for no less than 72 hours.
- h) Break down the samples to reflect the second stabilisation mixing process.
- i) Determine OMC/MDD with 60/40 slag/lime.
- j) Undertake UCS testing at 3%, 4% and 5% 60/40 slag/lime.

Application Rate, %	Field Target Spread Rate, kg/m ²
---------------------	---

Hydrated Lime (1 st Treatment)	3.0	18.0
60/40 Slag/Lime (2 nd Treatment)	4.0	15.5



Australian Pavement Recycling and Stabilisation Conference


Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Construction Phase

Date	Activity	Duration
10 April 2024	Prepulverisation and crossblending	1 day
12 April 2024	300mm lime stabilisation	1 day
13-15 April 2024	Amelioration	3 days
16 April 2024	Removal of 50mm of lime treated material	1 day
17 April 2024	Slag/Lime strengthening stabilisation	1 day
26 April 2024	Placement of SAMI seal	1 day
30 April 2024	Placement of 50mm AC wearing course	1 day



**Australian Pavement Recycling
and Stabilisation Conference**


Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Pavement Recycling and Stabilisation Association

Construction Phase




**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Construction Phase



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



AustStab

Pavement Recycling and Stabilisation Association

Construction Phase



Australian Pavement Recycling and Stabilisation Conference

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Post Construction Testing



**Australian Pavement Recycling
and Stabilisation Conference**




Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Pavement Recycling and Stabilisation Association

Post Construction Testing



Australian Pavement Recycling and Stabilisation Conference


Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Pavement Recycling and Stabilisation Association

Post Construction Testing








**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Post Construction Testing



Australian Pavement Recycling and Stabilisation Conference

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Pavement Recycling and Stabilisation Association

Project Economics

Item	Qty	Unit	Rate	Total Cost	% of total
Project management	1	item	\$ 19,191.67	\$ 19,191.67	6%
Geotechnical investigations/designs	1	item	\$ 16,080.00	\$ 16,080.00	5%
Site establishment/prelims	10	days	\$ 3,131.51	\$ 31,315.10	9%
Traffic control	12	days	\$ 1,604.89	\$ 19,258.68	6%
Initial seal	3720	m2	\$ 6.14	\$ 22,840.80	7%
40mm AC10 Asphalt	3185	m2	\$ 32.57	\$ 103,735.50	31%
Pavement stabilisation	2475	m2	\$ 39.11	\$ 96,797.25	29%
Earthworks/drainage	1	item	\$ 21,721.97	\$ 21,721.97	7%
			Total	\$ 330,940.90	



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience


Pullman King George Square, Brisbane • 7th August 2024



Pavement Recycling and Stabilisation Association

Conclusion

- River Tce challenges not unique
 - Height restrictions
 - Flood zone
 - Thin pavements
 - Variable materials
 - Wet construction period
- Crossblending very important
- Double stabilisation strategy
 - 3.0% Hydrated Lime, then
 - 4.0% 60/40 Slag/lime



**Australian Pavement Recycling
and Stabilisation Conference**

Designing for Reuse and Resilience

Pullman King George Square, Brisbane • 7th August 2024



Pavement Recycling and Stabilisation Association